

Data/ Specification Sheet

PYRO-CHEM® Carbon Dioxide Hand Portable Fire Extinguishers

FEATURES

- ULC Listed
- Simple, trouble-free operation and maintenance
- Features upright positive on-off operation utilizing squeeze-grip activation
- Non-corrosive, non-conductive, clean extinguishing agent leaves no residue
- Strong, impact-resistant discharge horn
- One person operation
- Suitable for use in temperatures from -40 °C to 49 °C (-40 °F to 120 °F)
- Six-year limited warranty

SIZES

2.3 kg (5 lb) to 9.1 kg (20 lb)



PART NO.	MODEL	UL RATING	EFFECTIVE RANGE	CAPACITY	DISCHARGE TIME	DIAMETER	WIDTH	HEIGHT
552087	CO2-050-I	5-B:C	1.5-1.8 m (5-6 ft)	2.3 kg (5 lb)	10-12 seconds	13.5 cm (5.3 in.)	25.4 cm (10 in.)	48.0 cm (18.9 in.)
552088	CO2-10-I	10-B:C	1.5-1.8 m (5-6 ft)	4.5 kg (10 lb)	10-12 seconds	17.5 cm (6.9 in.)	31.8 cm (12.5 in.)	54.1 cm (21.3 in.)
552089	CO2-15-I	10-B:C	2.1-3.0 m (7-10 ft)	6.8 kg (15 lb)	13-15 seconds	17.5 cm (6.9 in.)	31.8 cm (12.5 in.)	70.9 cm (27.9 in.)
552090	CO2-20-I	10-B:C	2.1-3.0 m (7-10 ft)	9.1 kg (20 lb)	15-17 seconds	20.3 cm (8 in.)	34.3 cm (13.5 in.)	71.1 cm (28 in.)

Underwriters Laboratories of Canada Listed

CLASS **B** **C** FIRES



PYRO-CHEM
One Stanton Street
Marinette, WI 54143-2542
715-732-3465
www.pyrochem.com

PYRO-CHEM is a trademark of Tyco International Ltd. or its affiliates.