

# Data/ Specification Sheet

## Dry Chemical Hand Portable Fire Extinguishers (ULC)

### FEATURES

- ULC Listed
- Meets or exceeds requirements of ANSI/UL 299 and 711
- Simple operation and maintenance
- Durable red powder paint finish
- Tough, glare-resistant, one-piece mylar nameplates
- Rechargeable
- Units are supplied with wall hanging bracket
- Large, easy-to-read pressure gauge
- Six year limited warranty from date of delivery to original end-user purchaser

### APPLICATIONS

PYRO-CHEM® dry chemical extinguishers are designed for protection of light and ordinary hazards. These compact and portable extinguishers are suited for both industrial and commercial fire protection needs. All extinguishers are designed to fit most wall mounted storage cabinets. Typical applications include light manufacturing, warehousing, restaurants, office buildings, shop areas, auto repair shops, paint process areas, welding areas, machinery, apartment buildings, parking garages, aircraft servicing areas, material handling vehicles, and many others.

### DESCRIPTION

- ▶ 1. Shells are produced by a cold deep draw process which yields a seamless steel cylinder with a high tensile strength.
- ▶ 2. PYRO-CHEM's unique pre-treatment of the raw low carbon steel not only consists of a cleaning process, but also applies a special lubricant which helps keep the interior and exterior shell surfaces scratch free.
- ▶ 3. The collar and specially preformed bottom enclosure are MIG welded to produce a smooth, high integrity weld.
- ▶ 4. Extinguisher shells are 100% factory air tested in excess of 41.4 bar (600 psi).
- ▶ 5. The powder paint process used by PYRO-CHEM is superior to conventional liquid based paint systems in its ability to resist blistering, cracking, fading, chipping and corrosion.
- ▶ 6. Before the extinguisher shells are painted, they are surface tested with a blasting or phosphate bonding process. This enhances the paint adhesion and corrosion resistance.
- ▶ 7. The specially formulated powder paint is electrostatically applied and oven cured to help ensure complete coverage and uniform paint thickness.
- ▶ 8. Easy grip extinguisher handles designed for maximum portability, allowing operators to fight the fire without removing work gloves.
- ▶ 9. Extinguisher valve bodies are made from a durable extruded aluminum alloy.
- ▶ 10. Completed valve assemblies feature plated steel valve stems which contain O-Ring and seat material compatible with the agent to provide reliable performance and long life.

11. Rugged all-steel pick-up tubes help provide proper and dependable agent flow through the valve body.
12. Extinguishers have large, color-coded pressure gauges which provide a quick visual indication of unit readiness.
13. Metal ring pins are utilized and held in place by a visual inspection seal to help prevent accidental discharges.
14. One piece, multilingual, mylar label with easy-to-read pictograms provides the user with step-by-step operating instructions and the hazard classes for which the extinguisher was designed. Label also contains useful recharge, maintenance, inspection, operating temperature, HMIS and model information.
15. Large, easy-to-scan bar coded model and ULC serial numbers simplify inspection and maintenance record keeping.
16. PYRO-CHEM valve subassemblies are 100% tested for functionality before final assembly.
17. Extinguishers are vacuum-filled at the factory to precise filling tolerances.
18. Pressurized to 13.4 bar (195 psi) and 100% leak tested utilizing mass spectrometry technology.
19. Injection molded nozzle tips are designed to tight specifications and maximize the extinguishment capabilities of the particular model and agent.
20. Extinguishers are shipped from the factory in individual recyclable corrugated cardboard cartons. Designed and field tested to help assure your extinguishers arrive undamaged and ready for operation. The glued one-piece cartons have carrying handles and a pressure gauge inspection port.
21. All extinguisher cartons are properly labeled according to the latest DOT regulations for ease of shipping in the field.
22. PYRO-CHEM's dry chemical extinguishing agents are manufactured from the high quality raw materials and are carefully blended to meet stringent performance specifications. These agents are then tested to be free-flowing, water repellent and electrically nonconductive.
23. As a final quality control step, extinguishers are randomly sampled for performance testing, which includes weight percent discharge and discharge times.

### AGENT

**ABC** – A monoammonium phosphate-based agent for use on Class A (wood, paper, cloth) and Class B (flammable liquids and gases) fires, and Class C (electrical) conductivity.

**PK** – A potassium bicarbonate-based agent which is the most effective Ansul agent for knock-down of Class B (flammable liquids and gases) fires and Class C (electrical) conductivity.

**BC** – A sodium bicarbonate-based agent for use on Class B (flammable liquids and gases) fires and Class C (electrical) conductivity.

### ORDERING INFORMATION

For fire protection assistance, see your nearest authorized PYRO-CHEM distributor or contact your PYRO-CHEM sales representative.



PYRO-CHEM  
One Stanton Street  
Marinette, WI 54143-2542  
715-732-3465  
www.pyrochem.com

PYRO-CHEM is a trademark of Tyco International Ltd. or its affiliates.

