

Data/ Specification Sheet

PYRO-CHEM® Model PWS-25G Pressurized Water-Type Fire Extinguisher 9.5 Liters (2.5 Gallons)

FEATURES

- Meets or exceeds ULC requirements
- Simple operation and maintenance
- Squeeze grip, positive on-off operation
- Brass chrome plated valve
- Waterproof stainless steel gauge
- Stainless steel shell
- Schrader valve for pressurization
- Easy service construction

DESCRIPTION

- The PYRO-CHEM® Stainless Steel Water Extinguisher can be utilized in many Class A hazards such as office environments and industrial locations, as well as warehouse and oxidizing chemical storage areas. The unit features a stainless shell and chrome-plated valve. The nameplate features easy to read step-by-step instructions for operating the extinguisher. The Schrader valve allows for easy recharge in the field.

SPECIFICATIONS

Model No.:	PWS-25G
ULC Rating:	2-A
Capacity:	9.5 L (2.5 gal)
Extinguisher Height:	64.8 cm (25.5 in.)
Width:	22.9 cm (9 in.)
Depth:	17.8 cm (7 in.)
Range:	10.7 m (35 ft)
Discharge Time:	Approximately 50 seconds
Bracket:	Wall mount
Temperature:	4.5 °C to 48.9 °C (+40 °F to 120 °F)



008137

ORDERING INFORMATION

Part No.	Description	Approximate Shipping Weight
► 552501	PYRO-CHEM Model PWS-25G Pressurized Water-Type Fire Extinguisher 9.5 L (2.5 gal)	4.1 kg (9.0 lb)



PYRO-CHEM
One Stanton Street
Marinette, WI 54143-2542
715-732-3465
www.pyrochem.com

PYRO-CHEM is a trademark of Tyco International Ltd. or its affiliates.