



STORED PRESSURE DRY CHEMICAL FIRE EXTINGUISHERS

SIZES 2.5 LB. (1.1 KG) TO 30 LB. (13.6 KG)

FEATURES

- UL Listed
- ABC Multi-Purpose (Ammonium Phosphate) or PDC Standard (Sodium Bicarbonate) Dry Chemical
- Easy-to-service (internal spring) valve
- Squeeze grip with positive on/off operation
- Durable red powder paint finish
- Suitable for use in temperatures from -65 °F to 120 °F (-54 °C to 49 °C)
- Clear anodized aluminum valve
- Units supplied with wall hanging bracket
- 2-1/2 and 5 lb. units also available with vehicle bracket
- Heavy-duty running board bracket available for 10-30 lb. units (sold separately)
- Six-year limited warranty



006978

PART NO.	MODEL	UL RATING	EFFECTIVE RANGE	CAPACITY	DISCHARGE TIME	DIAMETER	WIDTH	HEIGHT
552122 (552121)	ABC-025-B (w/Vehicle Bracket)	1-A:10-B:C	8-10 ft. (2.4-3.0 m)	2.5 lbs. (1.1 kg)	8-10 seconds	3 in. (7.6 cm)	4.5 in. (11.4 cm)	16 in. (40.6 cm)
552126 (552127)	ABC-050-H (w/Vehicle Bracket)	3-A:40-B:C	10-15 ft. (3.0-4.6 m)	5 lbs. (2.3 kg)	13-15 seconds	4.25 in. (10.8 cm)	5.5 in. (14.0 cm)	17.8 in. (45.2 cm)
552130	ABC-10-H	4-A:80-B:C	10-15 ft. (3.0-4.6 m)	10 lbs. (4.5 kg)	20-22 seconds	5.5 in. (14.0 cm)	9 in. (22.9 cm)	20 in. (50.8 cm)
552133	ABC-20-H	20-A:120-B:C	12-18 ft. (3.7-5.5 m)	20 lbs. (9.1 kg)	27-31 seconds	7 in. (17.8 cm)	10 in. (25.4 cm)	24 in. (61.0 cm)
552134	ABC-30-H	20-A:120-B:C	12-18 ft. (3.7-5.5 m)	27 lbs. (12.2 kg)	27-31 seconds	7 in. (17.8 cm)	10 in. (25.4 cm)	28 in. (71.1 cm)
552132	PDC-10-H	60-B:C	10-15 ft. (3.0-4.6 m)	10 lbs. (4.5 kg)	16-19 seconds	5.5 in. (14.0 cm)	9 in. (22.9 cm)	20 in. (50.8 cm)
552129	Cut-Away ABC-050-H	-	-	-	-	4.25 in. (10.8 cm)	5.5 in. (14.0 cm)	17.8 in. (45.2 cm)

Underwriters Laboratories Inc. Listed & U.S.C.G. Approved when used with Appropriate Vehicle Bracket.

ABC models for CLASS **A** **B** **C** FIRES

PDC model for CLASS **B** **C** FIRES



TYCO SAFETY PRODUCTS
One Stanton Street
Marinette, WI 54143 USA

Phone: 800-526-1079 or 715-732-3465
FAX: 877-329-7976 or 715-732-3569
www.pyrochem.com