

# Data/ Specification Sheet

## PYRO-CHEM® Carbon Dioxide Hand Portable Fire Extinguishers

### FEATURES

- UL Listed
- Simple, trouble-free operation and maintenance
- Features upright positive on-off operation utilizing squeeze-grip activation
- Non-corrosive, non-conductive, clean extinguishing agent leaves no residue
- Strong, impact-resistant discharge horn
- One person operation
- Suitable for use in temperatures from -40 °F to 120 °F (-40 °C to 49 °C)
- Six-year limited warranty

### SIZES

5 lb (2.3 kg) to 20 lb (9.1 kg)



PART NO.	MODEL	UL RATING	EFFECTIVE RANGE	CAPACITY	DISCHARGE TIME	DIAMETER	WIDTH	HEIGHT
552083	CO2-050-I	5-B:C	5-6 ft (1.5-1.8 m)	5 lb (2.3 kg)	10-12 seconds	5.3 in. (13.5 cm)	10 in. (25.4 cm)	18.9 in. (48.0 cm)
552084	CO2-10-I	10-B:C	5-6 ft (1.5-1.8 m)	10 lb (4.5 kg)	10-12 seconds	6.9 in. (17.5 cm)	12.5 in. (31.8 cm)	21.3 in. (54.1 cm)
552085	CO2-15-I	10-B:C	7-10 ft (2.1-3.0 m)	15 lb (6.8 kg)	13-15 seconds	6.9 in. (17.5 cm)	12.5 in. (31.8 cm)	27.9 in. (70.9 cm)
552086	CO2-20-I	10-B:C	7-10 ft (2.1-3.0 m)	20 lb (9.1 kg)	15-17 seconds	8 in. (20.3 cm)	13.5 in. (34.3 cm)	28 in. (71.1 cm)

Underwriters Laboratories Inc. Listed and USCG Approved

CLASS **B** **C** FIRES



PYRO-CHEM  
One Stanton Street  
Marinette, WI 54143-2542  
715-732-3465  
www.pyrochem.com

PYRO-CHEM is a trademark of Tyco International Ltd. or its affiliates.